

What Is Claimed Is:

- Sub  
Q2
1. A method for driving a hysteresis-exhibiting final controlling element, comprising the steps of:  
driving the final controlling element by a drive signal having a variable drive quantity;  
and  
correcting the variable drive quantity as a function of a change thereof over time.
  2. The method according to claim 1, further comprising the step of:  
forming an offset value signal on the basis of the change over time of the variable drive quantity, wherein:  
the step of correcting is performed in accordance with the offset value signal.
  3. The method according to claim 2, further comprising the step of:  
limiting the offset value signal to a maximum offset value.
  4. The method according to claim 3, wherein:  
the maximum offset value is variable and is changed as a function of zero crossings of the offset value signal.
  5. The method according to claim 4, further comprising the step of:  
reducing the maximum offset value when a counter reading exceeds a predetermined threshold value within a predefined time between two of the zero crossings.
  6. The method according to claim 5, wherein:  
the counter reading is formed from the offset value signal.
  7. The method according to claim 6, wherein:  
the maximum offset value is reduced more quickly when a second, higher threshold value is exceeded.

094445-083101

8. The method according to claim 2, wherein:

the offset value signal corresponds to a value of the change over time of the variable drive quantity.

9. A device for driving a final controlling element exhibiting hysteresis, comprising:  
a control device that includes at least one microcomputer and that forms a variable drive signal quantity for driving the final controlling element in accordance with at least one program executed by the at least one microcomputer, wherein:

the at least one program corrects the variable drive signal quantity as a function of a change thereof over time.

10. A storage medium in which a computer program is stored, the computer program causing a processing device to perform the steps of:

driving a final controlling element by a drive signal having a variable drive quantity;

and

correcting the variable drive quantity as a function of a change thereof over time.

0944745-083404  
107E90-54244660